



"5500NGX"

TB-5500NGXDS3

Tellabs 5500NGX DS3 Test Board
(w/ 440A Jacks)

Application:

The TB-5500NGXDS3 has 440A jack access allowing metallic wiring verification and DS3 signal acceptance testing to the DSX-3/4. Tester 1 will transmit a DS3 test signal to the DSX-3/4. At the DSX-3/4, Tester 2 will verify "good" DS3 signal being received on DSX-3/4 - CKT 1 OUT jack. Tester 2 will then transmit from DSX-3/4 CKT 1 IN jack to Tester 1 at 5500NGX Slot 1- RX1. Tester 1 will record that a "Good" DS3 signal has been transmitted and received.

TB-5500HDUDS3

Tellabs 5500HDU DS3 Test Board
(w/ 440A Jacks)

Application:

The TB-5500HDUDS3 has 440A jack access allowing metallic wiring verification and DS3 signal acceptance testing to the DSX-3/4. Tester 1 will transmit a DS3 test signal to the DSX-3/4. At the DSX-3/4, Tester 2 will verify "good" DS3 signal being received on DSX-3/4 - CKT 1 OUT jack. Tester 2 will then transmit from DSX-3/4 CKT 1 IN jack to Tester 1 at 5500HDU Slot 1 - RX1. Tester 1 will record that a "Good" DS3 signal has been transmitted and received. The wiring label on TB-5500HDUDS3 indicates the circuit designations for access to the 24 DS3 circuits.



"5500HDU"

Accessories:

600209XL

Carrying Case

Call for Pricing