# **Fujitsu**



## ST-FUJ4300DS1

Fujitsu Flashwave 4300 DS1 Streaker Card (w/ LEDs)

## Application:

The ST-FUJ4300DS1 provides a quick method to verify wiring via LEDs ("streak") from the Fujitsu FLASHWAVE 4300 DS1 slots to the DSX-1. The ST-FUJ4300DS1 verifies wiring continuity of 14 DS1 circuits. At the DSX-1, using bantam to alligator clips, simply ground the corresponding pins and the ST-FUJ4300DS1 will light the LED associated with that connection.



### TB-FUJ4300DS1

Fujitsu Flashwave 4300 DS1 Test Board (w/ Bantam Jacks)

## Application:

The TB-FUJ4300DS1 provides metallic access to 14 DS1 circuits via bantam jacks to perform continuity and signal acceptance testing from the Fujitsu FLASHWAVE 4300 DS1 slots to the DSX-1. Using a T1 test set, the tester can transmit and receive T1 signals to verify cable acceptance and continuity.



#### TB-FUJ4300DS3

Fujitsu Flashwave 4300 DS3 Test Board (w/ 440A Jacks)

#### Application:

The TB-FUJ4300DS3 provides metallic access to the three (3) DS3 circuits via 440A jacks from the FLASHWAVE 4300 DS3 card slot to the DSX-3/4. The TB-FUJ4300DS3 is ideal for test acceptance procedures and pretesting before turn-up dates. With test equipment, a technician can quickly identify opens, shorts, crosses, and transmit & receive DS3 signals between the FLASHWAVE 4300 and DSX-3.



#### STB-FUJ4300BITS

Fujitsu Flashwave 4300 BITS Streaker/Test Board (w/ LEDs and Bantam Jacks)

#### Application:

The STB-FUJ4300BITS provides both continuity testing and jack access for signal acceptance testing from the BITS card slot to the cross-connect wiring points.

150 Cooper Rd. (F-15) W. Berlin, NJ 08091

www.tagcords.com

**Telecom Assistance Group** 

Telephone: (856) 753-8585

Fax: (856) 768-7645